

Pallet Racking Type	Low Investment	High Storage Density	Easy to Adjust & Adapt	Individual Pallet Access	Handling Mixed Articles	FIFO* Possible	Bay Height	Loading Capacity	Compatible Forklift Truck Types
Standard Aisle	✓✓		✓✓	✓✓	✓✓	✓✓	≤7500mm	≤1,000kg UDL per pallet ≤8,000kg SWL per bay	Various
Narrow Aisle	✓	✓	✓	✓✓	✓✓	✓✓	≤12,000mm	≤1,000kg UDL per pallet ≤12,000kg SWL per bay	VNA Trucks (Wire Guided Or Guide Rails)
Drive In	✓	✓✓					≤10,000mm	≤1,500kg UDL per pallet	Reach Truck / Counter-Balanced Forklift
Pallet Shuttle System	✓	✓✓				✓✓	≤12,000mm	≤1,500kg UDL per pallet	Various
Pallet Flow		✓✓				✓✓	≤10,000mm	≤1,000kg - 1250kg UDL per pallet	Reach Truck / Counter-Balanced Forklift
Push-Back		✓			✓		≤10,000mm	≤1,000kg - 1250kg UDL per pallet	Reach Truck / Counter-Balanced Forklift
Mobile (Power Racks)	✓	✓✓	✓	✓✓	✓✓	✓✓	≤10,000mm	≤1,000kg UDL per pallet ≤12,000kg SWL per bay	Various

✓ Good Option

✓✓ Best option

*FIFO

First In First Out

**Standard Configurations, Larger bay heights and higher loading capacities possible